

Scope Example

This simple program shows how the C language handles scope.

```
/*
 * this is a do-nothing program that demonstrates the
 * scope rules of C.
 */
#include <stdio.h>
#include <stdlib.h>

/*
 * forward declarations
 */
void g(int);
void h(void);

/* the top-level definition */
int variable = 1;

/*
 * the main routine
 */
int main(void)
{
    /* scope is function main */
    int variable = 2;

    printf("main(%d):variable = %d\n", __LINE__, variable);

    /* now an inner block */
    {
        /* scope is the rest of this block */
        int variable = 3;

        printf("main(%d):variable = %d\n", __LINE__, variable);

        /* now an even more inner block */
        {
            /* scope is this block */
            extern int variable;

            printf("main(%d):variable = %d\n", __LINE__,
                   variable);
        }
        /* end innermost block */

        printf("main(%d):variable = %d\n", __LINE__, variable);
    }
    /* end inner block -- back to main block */

    printf("main(%d):variable = %d\n", __LINE__, variable);

    /* now let's show how functions interact with scope */
}
```

```
g(variable);

/* bye! */
return(EXIT_SUCCESS);
}

/*
 * now notice "variable" is a parameter
 * so it (effectively) overrides references to the
 * top-level variable
*/
void g(int variable)
{
    printf("g(%d):variable = %d\n", __LINE__, variable);
    /* now let's call another function */
    h();
}

/*
 * this function has no declarations, so
 * let's see what it prints
*/
void h(void)
{
    printf("h(%d):variable = %d\n", __LINE__, variable);
}
```