Homework 2

Due Date: November 2, 2000 **200 Points**

1. (*20 points*) Chapter 14, exercise 6
2. (*20 points*) Chapter 14, exercise 9
3. (*160 points*) This exercise asks you to determine how the various shells access environment variables, and test for a potential problem.

   a. Write a program called *envalter* to add environment variables to an environment and then spawn a subprogram. Your program should take the following arguments:

   –b *env* add the environment variable *env* to the beginning of the environment. *Env* may be an environment variable name or a name and value (*var* or *var*=*value*, respectively).

   –d *env* delete all occurrences of the environment variable *env* from the environment. If *env* is an environment variable name, delete all environment variables with that name. If *env* is a name and value, delete *only* those variables with the given name and value.

   –e *env* like –b, except the environment variable *env* is added to the end of the environment.

   program execute the *program* in the new environment

   Hint: use *execve*(2) to execute the program. Do not use *system*(3)!

   b. Write a second program called *shell* that determines whether a given shell uses the first or last search path in the environment. This program should take the following arguments:

   –f *dir* put the first *xyzzy* program in this directory (if not given, use the directory *xyzzy1*)

   –l *dir* put the second *xyzzy* program in this directory (if not given, use the directory *xyzzy2*)

   shell use the named *shell*

   Hint: Create two programs called *xyzzy.* One should print “it’s the first” and the other “it’s the last”. Use the program you wrote in part a to delete the current search path, and add two new search paths. The first adds a search path containing the directory with the first *xyzzy* to the front of the environment, and the second adds a search path containing the directory with the second *xyzzy* to the end of the environment. Then spawn a shell and see which program is executed.

   c. Bundle your programs into a distribution mechanism that works as follows. After un-taring the program, the recipient types “make” to compile (set up) both programs. The recipient can then type “./check *shell*” where *shell* is the name of a shell (either relative or full path name) and the program will print: one of:
   shell: uses the first occurrence of the environment variable
   shell: uses the last occurrence of the environment variable